

Flat Semi Automatic Label Applicator Machine MT-60



The machine adopts high precision intelligent electric eye and extremely reliable programmable logic controller (PLC) for label peeling, label outputting and labeling. Adhesive labels will be adsorbed to the labeling head by air pressure, and then will be labelled on the item.

Introduction

Semi Automatic Label Applicator Machine for plane surface MT-60 is for various kinds of products labeling, there is a large adjustable range for the bottle and lid. Suitable for all kinds of products which are flat.

The machine adopts high precision intelligent electric eye and extremely reliable programmable logic controller (PLC) for label peeling, label outputting and labeling. Adhesive labels will be adsorbed to the labeling head by air pressure, and then will be labelled on the item. And this machine is equipped with a coding machine, and is able to finish labeling and printing at the same time. Click to view our Code Printer Machine.

After you putting the objects on the instructed position, the machine will finish the labeling process.

Application

- Labeling on the flat surface of various items
- Labeling on the flat surface of square bottles filled by cosmetics and Drugs
- Labeling or anti-counterfeit labeling on the flat surface of various kinds of boxes
- Labeling on the surface of LCD screen, electronic components, and is widely applied in many industries, such as cosmetics, daily chemical, electronics, food and medicine.

Features

- Efficient, and the speed is up to 60 times / min.
- Labeling head is greatly adjustable, and can be used for labeling on various items.
- Excellent labeling effect, no wrinkles or bubbles.
- Adopts reputable PLC, sensor and other electronic components, and the performance is extremely stable.
- Could work independently or be coupled with production line.
- Modular design, convenient maintenance and low cost.

Specifications

Model	MT-60
Label speed	25-50times/min
Label accuracy	± 1mm
Min.label roll inner diameter	≥75mm
Max.label roll out diameter	≤Φ250mm
Label length	10mm -80mm
Label width	10mm -150mm
Product height	5mm -80mm
Power	120W
Voltage	220V 50Hz/110V 60Hz
Machine size	515x310x610mm
Machine weight	26kg