

## *NSL-160B Automatic Stripping Packaging Machine*



NSL-160B Automatic Strip Packaging Machine, be characterized of advanced structure, high efficiency, low noise and easy to operate. It utilizes frequency control to set travel at will, increase the vibration entire column feed mechanism and optical monitoring devices, it can automatic counting, and can Auto-complete filling, sealing, tangent, batch number, cut at high-speed operation. It applies to package the Tablets, capsules and Electronic Components in the pharmaceutical industry. It can make a good sealing and lucifuge well.

The machine shell is made of welded stainless steel plate by forming, the Machine is designed reasonable and every machine configured with safe operation of protective PC board door cover which is according to “GMP” demands. It enhanced aesthetics and practicality of products.

The entire device uses programmable controller and programmable touch screen to control each action point, so it can be ensure that uncoated or coated tablets and capsules can be automatic filling into two level of Alu materials became to strip packing, the length of strip sheet (the strip traction) can be change in the touch screen as your required, you just adjusts some rollers and remove some cutter easily when you want to change the strip packing length or different sheets,

The TEMP of heating sealing mould is control by intelligent temperature controller with PID system, meanwhile, the TEMP detector is adopts PT roller surface detector which components is

imported, on the one hand, it can ensure the stable TEMP of roller's surface, on the other hand, it can increase leak-proofness of heating strips.

The speed of main motor is controlled by transducer which is speed regulating, it adopts programmable controller, so it can make the drive of mechanical frame simple, easy to maintain. In addition, the machine also has a cutter in sealing station, which is for waster edge easy to tear, it can make the strips look more clearly and nice looking.

#### **Technical Parameters:**

Capacity: 30-48 thousand pcs/hour	Punch frequency: 40~80 times/min
Packaging area: 160mm× any length	Main motor power: 0.75KW
Material roll DIA: 300 mm	Total power: 2.75KW
Machine Dimension (L×W×H): 1300×750×1700 mm	Air compressor: 0.5Mpa
Packing Dimension (L×W×H): 1500×1000×1900mm	Gross weight: 900 kg