



## ***GZPT-series High-Speed Rotary Tablet Press Machine with Recompression Function***



This machine had realized on-line pressure checking, analyze and judgment, Automatically adjust powder filling depth, to achieve automatically control during tablet production period meantime monitoring punches & die situation and powder supply as safeguard which greatly reduce production cost, increase tablet qualified rate.

- 1) With feeding material automatic detection system.
- 2) The force feeder device could improve liquidity and filling for the granules.
- 3) With tablet Rejection function in bulk or singly by detection of compression pressure.
- 4) Advanced lubrication system, punches installed with oil proof loops, avoiding pollution.
- 5) Automatic PLC-Touch Screen Control System.
- 6) GMP standard.
- 7) EU toolings.

### **Technical Parameters**

<b>Model</b>	<b>GZPT-26</b>	<b>GZPT-32</b>	<b>GZPT-40</b>	<b>GZPT-45</b>
Type of Punch and Dies( EU)	D	B	BB	BBS
Qty of stations	26	32	40	45
Max tablet diameter(mm)	25	16	13	11
Max abnormal prolate axis size(mm)	25	18	16	13
Max. Working capacity(pcs/h)	170 000	210 000	260 000	280 000
Max. Filling Depth(mm)	20	18	18	18
Max. Main Pressure(KN)	100	80	80	80
Max. Pre-pressure	20	20	20	20
Idle load noise(DB)	<75			
Power	380V, 50Hz, 9.5KW			
Dimensions(mm)	780*860*1930			
G.W	1700			