

## *3114 Dual Action Tamp Label Applicator*



The Label-Aire Model 3114 Label Applicator represents the ultimate in dual action tamp pressure-sensitive labeling technology.

The Model 3114 Dual Action Tamp labeler is simply the most advanced two-panel labeler on the market with its intelligent controller, impressive speeds, and high accuracy.

The user-friendly 3114 Dual Action Tamp Label Applicator features Automatic label setup, Quick-Action collapsible rewind, and a large R3 digital display that is Rotateable, Remoteable, and very Readable. Adding to its versatility, the 3114 Dual Action Tamp can be oriented nose-up, nose-down or reels-up. With five onboard user-selectable languages, domestic or CE (European) configurations, and standard/metric unit display, the 3114 Dual Action Tamp can handle almost any PS labeling application on the planet.

Automatic setup with multiple programmable label pages for easy changeovers to different label sizes.

R3 digital display with five languages (English, French, German, Italian, Spanish) and detailed alarm message

Quick-Action collapsible rewind for easy removal of scrap liner.

Optional smart powered rewind for improved label accuracy and dynamic web tension control.

## Specs

- **Dimensions:** Height: 27" (685.6 mm), Length: 33.44" (849.3 mm), Width: 34.2" (868.7 mm)
- **Weight:** 140 lbs. (63.5 kg)
- **Standard Label Dimensions:** Max. Web Width: 4.13" (105 mm), Optional 7.13" (181 mm) Label Width, Min. Web Width: .63" (16 mm), Min. Label Length .38" (10 mm)
- **Label Packaging:** 12" (305 mm) O.D. rolls std. on 3" (76 mm) I.D. cores, Up to 16" (406 mm) rolls with optional 16" (406 mm) unwind
- **Dispense Speed:** Up to 1,500" (3,810 cm) of web per minute (standard), Up to 2,000" (5,080 cm) of web per minute with powered rewind
- **Label Dispense Accuracy:** +/-1/32" (.8 mm)
- **Electrical:** 115 Volts AC 60 Hz 3 Amps., 220 Volts AC 50 Hz optional
- **Air:** 4 cfm at 90 psi to 110 psi for most applications
- **Options:** 16" (406 mm) non-powered unwind, Smart 10" (254 mm) powered rewind, 6" (152 mm) label core adapter, Strobe signals for "low label" and "out of labels"