



Automatic Sleeve Wrapper J-5040A



J-5040A is suitable for wrapping products such as pop-cans and bottles, etc, it works with PE shrink tunnels.

Characteristic:

- The Machine adopts the advanced touch screen system for man-machine conversation, 'Omron' programmable logic controller (PLC), 'AirTAC' air-jar, and all the rest parts adopt international famous brand.
- Up and down magnetic switch prevent sealing mistakes, and protect the operators.
- Intelligent temperature controller performs stable.
- Large power conveyer motor, with stepless speed regulating, ensures smooth feeding.
- Up and down large power fan system ensures the excellent effect of shrinking in one time.
- Super cooling system cools the packing and makes the figuration perfectly.

Specification:

Model	QSJ-5040A
Voltage	3phase 220V/380V, 50-60HZ
Power	3KW
Capacity	0 - 10pcs/minute
Working air Pressure	0.4-0.6Mpa
Width/thickness of the Film	Max. 590mm/0.03 - 0.25mm
Max. Packing Dimension(L*W*H)	450*300*350mm
Min. Packing Dimension(L*W*H)	250*50*100mm
Machine Size(L*W*H)	1,060*1,600*1,930mm
Machine Weight	370kg

Model	BSE5040A
Power supply	3phase 220V/380-460V 50-60HZ
Heater power	20KW Adjuster
Conveyer speed	0-10m/minute
Tunnel size(L*W*H)	1500*500*460mm
Conveyer loading	30KGS MAX.
Machine size(L*W*H)	2500*820*1680mm
Machine weight	470KGS
Shrink film	PE,POF,PVC,PP