

## SPAF-H series Duplex Head Auger Filler (2 fillers)



This type of auger filler can do dosing and filling work. Due to the special professional design, it is suitable for the fluidic or low-fluidity materials, like milk powder, Albumen powder, rice powder, coffee powder, solid drink, condiment, white sugar, dextrose, food additive, fodder, pharmaceuticals, agriculture pesticide, and so on.

### Features

- The hopper could be washed easily without tools.
- Servo motor drive screw.
- Stainless steel structure, Contact parts SS304
- Include handwheel of adjustable height.
- Replacing the auger parts, it is suitable for material from super thin powder to granule.

### Technical Parameters

Model	SPAF-H(2-8)-D(60-120)	SPAF-H(2-4)-D(120-200)	SPAF-H2-D(200-300)
Filler Quantity	2-8	2-4	2
Mouth Distance	60-120mm	120-200mm	200-300mm
Packing Weight	0.5-30g	1-200g	10-2000g
Packing Weight	0.5-5g, <±3-5%; 5-30g, <±2%	1-10g, <±3-5%; 10-100g, <±2%; 100-200g, <±1%;	<100g, <±2%; 100 ~ 500g, <±1%; >500g, <±0.5%
Filling speed	30-50 times/min./filler	30-50 times/min./filler	30-50 times/min./filler
Power supply	3P, AC208-415V, 50/60Hz	3P AC208-415V 50/60Hz	3P, AC208-415V, 50/60Hz
Total Power	1-6.75kw	1.9-6.75kw	1.9-7.5kw
Total Weight	120-500kg	150-500kg	350-500kg