

SPAF-L Single Head Auger Filler



This type of auger filler can do measuring and filling work. Due to the special professional design, it is suitable for the fluidic or low-fluidity materials, like milk powder, Albumen powder, rice powder, coffee powder, solid drink, condiment, white sugar, dextrose, food additive, fodder, pharmaceuticals, agriculture pesticide, and so on.

Features

- The split hopper could be washed easily without tools.
- Servo motor drive screw.
- Stainless steel structure, Contact parts SS304
- Include hand-wheel of adjustable height.
- Replacing the auger parts, it is suitable for material from super thin powder to granule.

Technical Parameters

Model	SPAF-11L	SPAF-25L
Hopper	Split hopper 11L	Split hopper 25L
Packing Weight	0.5-20g	1-200g
Packing Weight	0.5-5g,<±3-5%;5-20g, <±2%	1-10g,<±3-5%;10-100g, <±2%;100- 200g, <±1%;
Filling speed	40-80 times per min	40-80 times per min
Power supply	3P, AC208-415V, 50/60Hz	3P AC208-415V 50/60Hz
Total Power	0.95 Kw	1.2 Kw
Total Weight	100kg	140kg
Overall Dimensions	561×387×851 mm	648×506×1025mm

Model	SPAF-50L	SPAF-75L
Hopper	Split hopper 50L	Split hopper 75L
Packing Weight	10-2000g	10-5000g
Packing Weight	<100g,<±2%;100 ~ 500g, <±1%;> 500g, <±0.5%	<100g,<±2%;100 ~ 500g, <±1%;> 500g, <±0.5%
Filling speed	20-60 times per min	10-30 times per min
Power supply	3P, AC208-415V, 50/60Hz	3P AC208-415V 50/60Hz
Total Power	1.9 Kw	3.75 Kw
Total Weight	220kg	350kg
Overall Dimensions	878×613×1227 mm	1141×834×1304mm