

## *3135 Wipe-On Label Applicator*



The Label-Aire Model 3135 Label Applicator makes labeling easier and faster...keeping you many steps ahead of your competition.

The Model 3135 Wipe-On Label Applicator delivers on its promise of speed, accuracy, and ease of use. And that translates into lower operating costs and increased productivity for your business.

Speeds up to 3,500 inches (88.9 m) of web per minute make the Model 3135 an ideal choice for demanding applications requiring high speed and precision. Advanced features include Automatic Speed Following (ASF) which allows product surface profiling, ensuring wrinkle-free labeling on even the most difficult product shapes and label materials (optional encoder required). Zero Downtime Labeling allows your production to continue without costly interruptions. Product/label queuing and missing label compensation virtually eliminate unlabeled products or missing lot and expiration codes.

Put this high-speed wipe-on pressure-sensitive technology to work for you all day, every day. The Model 3135 Wipe-On Label Applicator is built to meticulous quality standards and designed to withstand the most intense operation.

- **Automatic setup** with multiple programmable label pages for easy changeovers to different label sizes.
- **Stepper motor drive** for precise starting / stopping, increased reliability, wider range speed variability, and lower maintenance.
- **R3 digital display** offers selection of five languages (English, French, German, Italian, Spanish), domestic or CE (European) configurations, standard/metric unit display and detailed alarm messages. Can rotate 360°.
- **Automatic Speed Following (ASF)** provides accurately applied labels even through changes in product speed.
- **Quick-Action collapsible** rewind allows easy removal of scrap liner

## Specs

- **Dimensions:** Height: 32.68" (.83 m), Length: 41.25" (1.048 m), Width: 24.6" (.63 m)  
Weight: 180 lbs. (84 kg)
- **Standard Label Dimensions:** Max. Web Width: 7.13" (181 mm), Min. Web Width: 1" (25 mm), Min. Label Length: .5" (13 mm)
- **Label Packaging:** 20" (508 mm) O.D. rolls std. on 3" (76 mm) I.D. cores with optional 6" (152 mm) core
- **Dispense Speed:** 3,500" (8,890 cm) of web per minute
- **Label Dispense Accuracy:** Up to +/- 1/64" (.4 mm)
- **Electrical:** 115 Volts AC 60 Hz 3 Amps., 220 Volts AC 50 Hz optional
- **Options:** Encoder kit for Automatic Speed Following, 6" (152 mm) label core adapter, Hot stamp imprinter, Model 2700 T-Base stand, Strobe signals for "low label" and "out of labels"