TINTITU"

Automatic L-Sealer Cutting Machine BSF-5640LG



BSF-5640LG Auto L-Sealer is your best effective and economical choice for smart roomy facility layout. With packaging speed up to 25 PPM. Automatic L Bar Sealer is mainly applied to film wrapping for different products, which has the advantages of dustproof, damp-proof and beautiful sealing.

- Widely applied to different kinds of products
- Economical model which is the best choice for getting started with automatic sealer
- Equipped with safety protection cover and alarm device
- Automatic feeding, whose length can be automatically adjusted by combination of sensor and timer
- Design of brush is for permanent use
- Sealing temperature is controlled by PID system
- Safety protection & alarm
- Isolated perforating rod for easy adjustment without tearing line
- Easy operation & adjustment
- High efficiency to maximize capacity
- Temperature, Sealing Time, Sealing Height adjustable

Parameters:

| Model | BSL-5640LG |
|-------------------------------------|-----------------------------|
| Voltage(V/Hz) | 220V 50/60HZ |
| Air Pressure Required(kg/cm³) | 5-8 |
| Power (kw) | 1.8 |
| Capacity (PCS/min) | 0-25 |
| Max Packing Size (mm) | W+H<450, W<400, H<120,L<350 |
| Max Sealing &Cutting Size(L×H) (mm) | 500×400 |
| External Dimension (L×W×H)(mm) | 1770×830×1600 |
| Net Weight (kg) | 300 |