

## WP-E series Vertical Packaging Machine



### Application

- ◎ Applicable Bag Type: pillow bag, gusset bag, seal type bag, triangle bag.
- ◎ Applicable Film Material: a variety of laminated films, single layer PE film. Film thickness range 0.03~0.15mm.
- ◎ Applicable Packing Materials: a variety of snack food, frozen food, milk powder, pet food, coffee, oatmeal, sugar, salt, puffed food, rice, herbal, tea, small hardware, etc.

### Feature

- ◎ PLC control, man machine interface, easy to operate and maintain.
- ◎ Equipped with servo motor and optical tracking devices to keep accuracy and high speed.
- ◎ Machine frame is made by stainless steel #304, equipped with auto-stop protection function when open the door.

### Technical Parameters

Model	WP-E3220	WP-E4230	WP-E5235
Film width	120~320mm	140~420mm	180 ~ 520mm
Bag size	L: (40~210)mm	L: (40~330)mm	L: (40~350)mm
	W: (50~150)mm	W: (60~200)mm	W: (70~250)mm
Packing speed	65 ( bags/min)	60 (bags/min)	60 ( bags/min)
Film pulling driven system	servo motor	servo motor	servo motor
Horizontal sealing driven system	cylinder	cylinder	cylinder
Voltage	2.2KW/220V/50(60)HZ	3KW/220V/50(60)HZ	3.2KW/220V/50(60)HZ
Gas Pressure	0.4~0.8MPa	0.4~0.8MPa	0.4~0.8MPa
Gas Consumption	0.5m³/min	0.6m³/min	0.6m³/min
Machine Size(mm)	1326*1066*1503	1596*1166*1708	1696*1276*1808
Machine weight	380KG	450KG	540KG

<b>Model</b>	<b>WP-E6240</b>	<b>WP-E7245</b>
Film width	200~620mm	230~720mm
Bag size	L: (40~400)mm	L: (40~450)mm
	W: (90~300)mm	W: (105~350)mm
Packing speed	50 ( bags/min)	50 ( bags/min)
Film pulling driven system	servo motor	servo motor
Horizontal sealing driven system	cylinder	cylinder
Voltage	3.5KW/220V/50(60)HZ	3.8KW/220V/50(60)HZ
Gas Pressure	0.4~0.8MPa	0.4~0.8MPa
Gas Consumption	0.8m <sup>3</sup> /min	0.8m <sup>3</sup> /min
Machine Size(mm)	1900*1400*1920	1996*1496*2138
Machine weight	540KG	850KG