

Pneumatic L-Seal Cutting Machine BSL-5045LA



BSL-5045LA can convey the products automatically into shrink tunnel through conveying belt for shrink packaging after sealing & cutting. Equipped with shrink tunnel to reach higher working capacity.

- Safety device that prevents the sealing knife from overheating and guarantees operator's safety
- Nano-fiber cutter holder and anti-sticking thermostable chrome cutter that ensure good sealing without cracking or coking.
- Discharge conveyor removes the package to the shrink tunnel when the seal is complete.
- Conveyor belt height is adjustable via hand wheel.
- Time relay that ensures accurate control of sealing & cutting times.
- Electro-magnetic hold-down provides more secure seal.
- Sliding roll holder, fully adjustable for different sized rolls of film (max. width: 550mm).
- Return cylinder equipped to control sealing & cutting frame.
- BSL-5045LA is equipped with pneumatic mechanism.

Application:

1. The machine is designed to pack electronic products, hardware, software, foodstuff, printing, pharmacy, floor, ceramics, etc. in small amount.
2. It is suitable for all kinds of packaging materials, such as PVC, POF, PP, etc.

Parameters:

Model	BSL-5045LA
Voltage(V/Hz)	220/50
Air Pressure Required (kg/cm ³)	6-8
Power (kw)	1.2
Capacity (PCS/ h)	800-1200
Max Packing Size (mm)	W+H<450, W<400
Max Sealing &Cutting Size(L×W) (mm)	500×450
External Dimension (L×W×H)(mm)	1560×757×1040
Net Weight (kg)	135