

QL5545 Automatic L Sealer



QL5545 automatic L-type sealer characteristic:

1. The sealing knife adopts copper alloy sprayed with teflon, it won't stick film, sealing fastness, without smoke, non-pollution. Horizontal and vertical sealing knife adopt whole connecting without gap, the film won't break. Sealing frame adopts high quality alloy steel, the sealing quality is stable, frame difficult to be damaged.
2. The machine has entire automatically system, it equipped with sensors can reach high speed automatical working.
3. It is convenient to adjust according to different sizes products, just adjust the handle wheel can reach it, operation is easy.
4. It can be connected with production
5. It has protection function to avoid sealing product wrong and ensure the safety of operator

BS-D4520 shrink tunnel characteristic:

1. It adopts Schneider AC contactor, high-power Solid state booster and intelligent temperature controller to make temperature system more accurate, prolong the working life.
2. It adopts solid roller conveyor, the rollers wrapped with high temperature silica gel tube. It can stand heavy product and difficult abraded (you can choose net type conveyor)
3. It adopts high-power fan motor to ensure enough strong wind to reach perfect packing effect.
4. Inside wall adopts stainless steel, it has fast temperature transfer, even heating, low energy consumption, long working life characteristics.

Application:

This machine is widely used in foodstuff, drinks, printing, pharmaceutical, floor, hardware and other industries shrink packaging. It is suit POF, PE, PVC and other packaging material

Optional Items:

- Inlet conveyor
- connecting device (for packing small products)

Specification:

Model	QL5545	BS-D4520
Max packing size (mm)	L450×W350×H100	W450×H200
Max sealing size (mm)	L550×W450	/
Power (KW)	январь.30	08.май
Capacity	0-25 pcs/min	0-15 pcs/min
Voltage	220V 50/60HZ	380V 50/60HZ
Sealing Temperature	160°C— 240°C depends on thickness of film and environment temperature	160°C—240°C depends on thickness of film and environment temperature
Thickness of film(mm)	0.015—0.10	0.015-0.10
Air pressure(Kg/cm²)	5	5
Packing Material	POF PVC	POF PVC
Machine weight(kg)	320	210
Machine size (mm)	L1700×W900×H1400	1700*900*140