

Plastics Injection Molding Machines MSTX250A/PET



Master Packing joint with Ningbo injection company to supply customers with 10T-4,000T, injection weight 45g---40,000g, more than 30 kinds of specification injection mold machine. Master injection machine has energy-saving, environment-friendly, low noise, high rigidity, excellent performance, fast response, and high efficiency. With advanced servo motor and famous brand parts, Master injection machine becomes many customers' optimal choice for Injection needs.

Technical Parameter:

DESCRIPTION	MSTX250A/PET	
International size rating	250-1200	250-2400
INJECTION UNIT		
Screw diameter	65	75
Screw L/D ratio	25	25
Shot volume(therretical)	912	1546
Injection weight(pet)	984	1668
Injection rate	315	481
Injection pressure	133	156
Screw speed	180	175

CLAMPING UNIT		
Clamping force	2500	2500
Open stroke	540	540
Space between tie bars(WxH)	580x580	580x580
Max. Mould height	550	550
Min.Mould height	200	200
Ejector stroke	170	170
Ejector force	99	99
Others		
Max.pump pressure	17.5	17.5
Pump motor power	22	37
Heating power	24.5	36.8
Machine dimension(L×W×H)	5.9×I.6×2.3	6.4×l.6×2.3
Oiltank cubage	340	510
Machine weight	7.5	8.1