



JR-01(S) Rotary Filling&Capping Machine



It is specially used for lipgloss, liquid lipstick, lip pud, lip oil and mascara by adding optional function.

Features

JR-01(S) is a mature design meet with FDA cosmetic standard. It is a multifunctional filling machine for both hot and cold filling purpose, which has below characteristics

1. Fast Cleaning Within 3 min—complete the disassembling & cleaning, save the labor cost during production
2. 0-50ML Filling Volume Changeable Within 5min-change different spares to achieve different filling volume: 0-14ML, 10-50ML;
3. Since the valve is fast joint design, mascara and lipgloss could be used on one machine by fast changing spare.
4. Special movement control design ensure the electrical cam running;
5. Servo Filling system with nozzle lift up-down, achieve the bottom filling function to avoid bubbles during filling.
6. Program setting for auto cap lift up/down before capping, can set times (1-5 etc)
7. Wide application: can be used for lipgloss, liquid lipstick, lip pud, lip oil and mascara by adding optional function.

Technical Parameters

Basic Info		Configuration		Characteristics	
Dimension	Refer to the layout	Touch Weinview	Screen	<div>1pcs*20L Dual Layer SS304 Tank, inner layer is SS316L. With Heating and Mixing</div> <div><div>• 1pcs*20L Single layer SUS316L tank, with inner piston</div></div> <div>Mixing Speed is adjustable.</div>	
Voltage	AC220V,1P,50/60HZ	PLC:	Mistubishi		
Power	3.8KW	Filling	Mistubishi Servo		
Air Supply	0.6~0.8Mpa,≥300L/min	Cylinder	Airtac		
Capacity	32-40pcs/min（According to operator's speed）	Mixing Motor	JSCC	<div>• Piston filling adopts servo driven</div> <div>Container lifting up adopts servo driven .</div>	
Filling Volume	0-14ml, 10-50ml（By changing Spares）	Sensor	Omron		
Tank Volume	Dual layer Heating tank: 20L Single layer Pressure tank: 20L	Electrical Part	Schnedier		
Temp.Control	Able to control (if any)	Moving Controller	Mistubishi		
Nozzle	Single nozzle filling, container can be lift up/down				