

Sticker Labelling Machines LABELSTIK-120C. Twin



The Automatic Sticker Labelling Machine Model LABELSTIK-120C-Twin, is one of the most user friendly. The Machine incorporates latest sophisticated Micro Processor Control Label Dispensing system with user friendly Sensing system for Label and Product. The machine is suitable for applying Two Side Security Labels in "L" Shape on Two side of Cartons with speed upto 120 Products per minute depending on cartons and label size. Machine can be used for Self Adhesive Paper Labels, Film Labels or Hologram. It is capable of Labelling up to 120 units per minute depending on Product Size, Shape, Product movement direction and Label size. Machine suitable for all type Cartons.

Machine can be used for Offline or Online application, however customer require to send us sample of cartons and also detail of carton position while movement as the position of carton is important and required to feed and desired position for two side label application. LABELSTIK-120C.Twin Machine having required all basic features as a standard fitment to match the current market needs and also saves cost and time. Machine also available with optional special features of applying Twin Label on products from Single Label Roll or application of Label on product at regular intervals.

Technical Specifications:

Label Height	8 mm to 70 mm Standard*
Label Length	12 mm Standard*
Label Roll Dia.	400 mm
Core Dia.	75/76 mm
Gap Between two Labels	аррх. 3 mm
Product Feeding	Cartons required to feed on machine with regular interval/gap between cartons in required position by customer or required to feed manually by operator on machine in required position.
Electrical	220 VAC Single Phase Power Supply (50/60 Hz)
Power	1.0 Hp, 1.5 Amp.
Capacity	0.75 Kw
Speed	LABELSTIK-120C.Twin up to 120 Labels per minute LABELSTIK- 250C.Twin up to 240 Labels per minute. Speed of Machine depending on Label Size and Carton Size.
Direction of Product Movement	Left to Right from operator side for Glue Labelling and Right to Left from operator side for Sticker Labelling*
Conveyor height	830-875 mm*
Overall dimension	2440 mm(L) X 1300 mm(W) X 1600 mm (H)
	with T.G. Cabinet 2440 mm(L) X 1300 mm(W) X 1600 mm (H)
Machine Direction of Movement	Left to Right from operator side
* Specification can be changed as per customers requirements	