

HLSY mixing granular



Tinyard Enterprise Co., Limited is one of the top level China mixing granulator manufacturers and suppliers, welcome to wholesale mixing granulator from our factory.

Use:

Suitable for mixing and granulation of various materials in pharmaceutical, foodstuff processing and chemical industry.

Features:

- Meets GMP standard.
- The journal is sealed with clean air.
- High homogeneity with three-dimensional stirring and mixing.
- Granules become solid and homogeneous.

Working efficiency is 4-5times raised by a single process of mixing and granulation.

- Adhesive consumption is saved by 15-25% and drying time is reducedd.
- Easy operation with a meter showing work conditions.
- With a complete safe protection device to ensure the safest production.

HLSY-100B High-efficiency Mixing Granulator is a modified model of HLSY-100A, whose electric control part has installed PC computer control and can program 5-8 programs and access 50 menus of prescription, this making the produced granules rounder and smoother.

Main specifications:

Model	HLSY-100A、B	HLSY-10A
Volume	100 L	10 L
Material Charge Amount	35-45 kg	1-3 kg
Stirring Paddle Speed	4-250 r/min	430-660 r/min
Twisting Cutter Speed	100-3000 r/min	1500-3000 r/min
Motor for Sirring	7.5kw	0.8/1.1 kw
	1460 r/min	930/1410 r/min
Motor for Cutting	2.2 kw	0.55/0.75 kw
	2850 r/min	1430/2800 r/min
Weight (kg)	1300	180
Overall Dimensions(mm)	1700(L)×680(w)×1720(H)	930(L)×320(w)×1220(H)
Production Cycle	7∼15min	