

High Speed Pillow Bag Packaging Machine XY-90BZ-720



Application for the automatic vacuum packing machine:

Leisure food: potato chips, biscuit, jelly, confectionary, sweet, beans, shack food

Agriculture product: rice, dry fruit, cereal, vegetable (onion, potato, etc), spicy

Frozen sea food: meat ball, dumpling, prepared food

Industry products: connectors, rubber part, hardware part

Pharmaceutical industry: pills, small granule bags

Main feature for the automatic vacuum packing machine:

1. Can be used for Polyethylene Film Sealing by changing correspond parts
2. Can equip with whole punching system to punch hole on the bag for handling.
3. Machines' body and touching parts is stainless steel 304 as regeust.
4. Hole punching blade, continue bags, gusset bag device after your special request
5. Has fault display system, easy to operate and maintain.

Technical data:

Model	XY-90BZ-720
Sealing form	Back Sealing (pillow bag)
Measuring Scope	200g~5000 g/bag (special one can be customized)
Bag Size	L: 50~600mm W:150~350mm
Input Voltage	220V/50Hz 1 phase
Power	3.0 kw
Machine Weight	600KG
Machine Size	1400x1400x1500(L x W x H mm)
Packing material	Composite material such as POPP/CPP, POPP/VMCPP, CPP/PE etc. For example, the packing material is composed of glass paper, paper, polyester film, aluminum foil and with compound high pressure polyethylene coated inside. Outer circle should be flat, OD is less than or equal to 360mm, skeleton ID is equal to 75mm, film width is less than or equal to 420mm.
Work Condition	Temperature: -5 degree centigrade to 45 degree centigrade, no freezing.
	Relative Humidity: 30-85%, no dewing.
Powder Source	Compressed air (without water after filtering) 0.6x10 ⁵ Pa
Total Air Consumption	350L/min