

SN-600WT Shrink Packing Machine



Feature:

1. Imported PLC control, reduce the mechanical contact, the system more stable, reliable, easier maintenance.
2. Using Japan's Panasonic servo, to achieve infinitely variable speed control, the process can be dynamically adjusted.
3. New longitudinal sealing heating, can be sealed at low temperature, reduce downtime hot film.
4. Shrink furnace efficient dual-zone, automatic temperature control.
5. Efficient hot air circulation to ensure the quality of contraction.
6. The use of film, automatic filling, sealing, cutting, fast packaging speed.
7. With digital display, can directly display the film size, packaging speed, output, temperature, etc.
8. Servo speed, convenient and simple. Picture as the basic type, according to the need for local changes.
9. Unmanned operation of the feeding system, configuration of various forms of conveyor, to ensure that the location of the material will not deviation.
10. Anti-cutting safety clutch device, does not damage the packaging.
11. Can be connected with the production line to achieve unmanned automation.

Technical Parameters:

| Model | SN-600WT |
|--------------------|---------------------------|
| Film width | Max.600mm |
| Bag length | 200-650mm |
| Bag width | 100-280mm |
| Product height | 40-100mm |
| Film roll diameter | Max. 320mm |
| Packing speed | 30-100bags/min |
| Power | 220V/380V50HZ |
| Machine size | (L)5050×(W)1000×(H)1700mm |
| Machine weight | 1400Kg |