TINTITU"

Rice Vacuum Packaging Machine HVC-510T/2A



It is a commercial-grade vacuum packaging machine. It shares many characteristics with larger models, such as heavy duty oil-filled rotary vacuum pumps, sealing systems, and all-metal construction, but has a vacuum chamber designed for bags no wider than 10 inches.

- Typical customers of the HVC-510T/2AMK2 include restaurants, food retailers, and supermarkets.
- Extremely easy to operate.
- Rugged all stainless steel chassis.
- Table top model, mounted on anti-slip rubber stands.
- All areas in contact with product made with PTFE or stainless steel.
- Rear opening for oil level indicator.
- Equipped with two seal bars
- Five Programmable memory settings
- Programmable vacuum duration (in seconds).
- Impulse seal time adjustment (in fractions of a second).
- Cooling Time adjustment (in fractions of a second), decreases the risk of seal breach by allowing the bag to regain strength after seal cycle.

Parameters:

Model	HVC-510T/2A
Voltage (V/Hz)	AC 380/50 220/50 110/60
Motor power (W)	900
Sealing Power (W)	600
Ultimate Vacuum Pressure (Kpa)	1
Sealing Width (mm)	10 or 2×3
Chamber Dimension (L×W×H) (mm)	550×550×140
Vacuum Pump capacity (m3/h)	20
Material for Vacuum Chamber	SUS304
External Dimensions (L×W×H) (mm)	600×650×500
Net Weight (Kg)	Approx.91