

RL 422 Twin Tube Packing Machine



Main performance and functional characteristics:

- Equip with safety protection, and comply with firm safety management request;
- Use double feeding packing fabrication, fast packing speed, high efficiency, covering a little area, saving resources;
- Adopt importing PID automatic adjustable temperature controller to ensure the neat and artistic seal mouth;
- Use PLC Servo System and super touch screen to form the drive control center; maximize the whole machine\'s control precision, reliability and intelligentized level;
- Touch screen can store the technical parameters of various products, no need to reset while products changing;
- The left and right sides can pack the different products with different weight and sizes. If one part stops, the other part will not be influenced;
- Make different bag shapes and punching holes according to customers\' requirements;
- The body structure is made of stainless steel, artistic and durable.

Selected installations:

- ✓ Linked bags or multi-bags cutting functions;
- ✓ Pothook holes punching function (circle hole and other different abnormal holes);
- ✓ Different back seal patterns available;
- ✓ Gusseting device, bags with self-standing functions.

Usage:

Suitable for measuring and packing anomalous lumpish and granule materials, such as candy, popped food, biscuit, roasted seeds and nuts, granulated sugar, deep-frozen food, milk powder, mild tea, amylum, sauce and so on.

Technical Parameters

Model	RL422
Bag size	(L) 80-300mm
	(W) 80-200mm
Film width	Max.420mm
Film thickness	0.04-0.10mm
Measuring range	Max.1000ml
Packing speed	80-160 bags/min
Air consumption	0.65Mpa, 0.6m ³ /min
Packing material	All laminated film such as PET/PE, PET/AL/PE, Nylon/PE, etc.; PE (confirm when order)
Power supply	220V/380V 50-60Hz
Power	6kw
Dimension	L2000 x W1320 x H1750mm
Weight	800kg