

DPP-260H AL-PVC/AL-AL Blister Packaging Machine



DPP-260H Aluminum Plastic Packing Machine with advanced performance, simple operation, high output is the latest improved equipment in our company. It is the best ideal packing equipment for large and medium-sized pharmaceutical plant, health care factory and food industry.

Features:

- ◆ Adopts top brand PLC controller with touch screen displayed in Chinese and English, Frequency inverter for speed control, servo traction, which can ensure the length of blister traction adjustable within the range.
- ◆ With thermal temperature control and test, main machine over loading protect, PVC and PTP packing material position test, feeder material position test, failure automatic debug and alarm, automatic protection and stop running.
- ◆ The machine station module type design of level frame, good sight, safe and convenient operation.
- ◆ Thermal with contact type, positive press formed, air cushion thermal seal upper and lower net, photo register make your product package better.
- ◆ PVC exchange support with bigger type material support, whole roller, which makes the equipment more practicability.
- ◆ The special design of moulds in rectangle shape, ladder type fixing, provide much convenience and easy to moulds replacement. All material contact parts adopt high quality stainless steel and aluminum metal, slap-up surface treatment craft.
- ◆ Discharging finished product in right order, automatic collection of bad products, auto rewinding of strap material to ensure easy collection.
- ◆ Feeding efficiently, reliable and suitable for many kinds type arrange and irregular feeding, (according to actual product design fit feeder)
- ◆ The machine has been designed into separated body, which is easily move into lifts or workshops.

Technical Parameters

Item		Spec.
Standard cutting speed		Plastic/AL: 20~50cut/min
		AL/AL: 15~30cut/min
Max forming size		Plastic/AL: 250*110*22
		AL/AL: 250*110*18
Stroke range		Max. 30~140mm
Blister size	Standard	40*120mm
	Optional	88*57mm/95*65mm/100*43mm(or buyer's size)
Capsule quantity		According to buyer's needs
Material range(coreΦ75)	PVC sheet	(0.15~0.4) * 260*(Φ600) mm
	Sealing AL foil	(0.02~0.15) * 260 *(Φ300)mm
	Forming AL foil	(0.16-0.2) * 260 *(Φ600)mm
	Medical grade paper	(50-100)g/m ² *260*(Φ300) mm
Heating power	Upper heat-plate	2kw
	Lower heat-plate	2kw
	Sealing	2kw
	Coding	0.175kw*3pcs
Main motor		2.2kw
Total power		380V 50Hz 9.6kw
Air source		≥0.25m ³ /min/ 0.6~0.8Mpa(prepared by user)
Cooling of die		60~100L/h (tap water or recycling water)
Overall size (L*W*H)		4500 *760*1620(Two parts, including the leveling feet)
Weight of machine		About 1800kg