

YS-CS-3620-CP Vertical Packaging Machine



- Continuous pull film movement, Simple structure, Economical and practical
- Continuous motion leads to high productivity
- Lean machine concept enables cost-effective production
- Maintenance-free servo-technology ensures reliable production
- PLC controls enable precise machine movements for smooth production and good bag quality
- Intuitive HMI allows easy operation and short training time
- Open machine concept for easy access and maintenance
- Compact machine design for good ergonomics, product-conserving filling and saving space

Technical Parameters

Model	YS-CS-3620-CP-G	YS-CS-3620-CP-GB	YS-CS-3620-CP-4H-B
Bag type	Pillow bag 4 corner seal bag	Gusseted bag	4 corner seal bag
	+bottom block	+bottom block	+bottom block
Standard capacity	10-110 bags/min	10-110 bags/min	10-110 bags/min
Pillow bag	Width : 60-360mm	Width : 60-360mm	
	Length: 60-500mm	Length: 60-500mm	
Gusseted bag	Width : 50-330mm	Width : 50-330mm	Width : 50-330mm
	Depth : 45-140mm	Depth : 45-140mm	Depth : 45-140mm
corner seal bag	Front width:65-170		Front width:65-170
	Side width : 45-110		Side width : 45-110
please note:(1.5*front width+side width)<400,side width not Include corner sealed			
Film parameter	packaging material:OPP/AL/PE, PET/VMPET etc.		
	Film diameter: ≤600mm		
	Core diameter:76mm		

Total power	5 KW
Air pressure	≥0.5MPa
Air consumption	HS closure, 0.32NL/cycle
Outer dimensions (appr.)	2000*1500*2060mm
Weight (appr.)	780kg
Power supply (optional)	3N-PN-50Hz 380V/220V (3P 5 wires)