

TODAY MACHINE

Simple & Responsible Since 2001

Powder/Granule+Liquid/Paste 2 in 1 Packaging Machine VFFS-280/450(C+L/P)



Powder + Liquid

Powder + Paste

Granule + Liquid

Granule + Paste

Standard:

- Closed sealer housing
- Intuitive operator guidance on the button/touch panel
- Integration of all identification systems
- Printed mark identification & measurement of bag lengths
- Use of different heat sealing and welding instruments
- Minimal time required when changing rolls
- Stop when film roll end. Detect the fault automatically.
- Seal tight, no leaking.

Available option:

- Stainless steel and Paint version
- Display panel: Touch screen and Button screen
- Date & batch printer
- Date embossing system
- Sponge system, more/less air inside the packet
- Easy tearing notch
- Round and euro-hole punch, carrying handle punch

- Insulation and stirring system
- Numerical control cutter system, 1-99 packet
- Flat bottom package with center seal
- Frequency control system, less noise
- Power supply: – 110V, 120V, 220V, 240V. – 50Hz, 60Hz.

Technical parameter:

Model	VFFS-280C+L/P	VFFS-450C+L/P
Film width	Max 300mm,14"	Max 420mm,18"
Bag size	L: 40-175mm,2-7"	L:50-275/295mm,3-12"
	W:10-145mm,2-6"	W:60-195mm,3-9"
Output	30-70pcs/min	15-40 pcs/min
Bag type	Pillow seal	Pillow seal
	3 side seal	gusset seal
	4 side seal	
	gusset seal	
Packing range	C: 1-20g, 10-100g.	C: 100-500g, 500-1000g.
	L: 5-45ml,20-100ml,50-280ml	L: 5-45ml,20-100ml,50-280ml
Dimension	1100x1250x1700mm	1200*1300*2000mm
Power	2.2KW	2.8KW
Weight	300kg	380kg