



DZB Flow Wrapping Machine



This is mainly applied to the packaging of biscuit, betel nut, snowy biscuit, snowy ice-lolly, yolk pie, instant noodles, chocolate, candy, western snacks, tableware for aerial food, transparent soap, hotel articles, wet tower, gauze mask, IC card, cartoon card, electric components, trademark, little hardware etc. block-shaped things in the industries such as food, daily chemistry, cosmetics, hardware, electronics etc. It has the function of anti-moisture, dustproof and photonegative, and also enhances the product level and additional value. It can save more than 20% cost than using the manual packaging, and it can combine the aluminum plastic packaging machine and thermal contraction-packaging machine to manufacture.

Feature

- Compact and reasonable structure, stable and advanced performance, easy and convenient operation.
- Double frequency inverter control, and step less variable speed.
- The length of bag can be set and be cut at any time, no need to be trailed operation on one step, and save time and film.
- Adopt international famous electric components, PLC control, friendly interface, with convenient and rapid setting of parameters.
- The indication of fault is clear, and function is more humanized.
- Highly sensitive electric-eye color code tracing, which can make the sealing position be more accurate.
- Accurate temperature setting, which is suitable for all various of packing materials and enhances the quality of seal.
- Set the function of positioning power-off, without sticking to the blade and no waste of film.
- Simple and clear transmission system with more reliable work and more convenient maintenance.

- The control is realized through the soft, which facilitate the function regulation and technology upgrade, and they can also satisfy the production requirement.
- Automatic feeder device on the blister, which is suitable for the automatic feeding for aluminum plastic dosage panel with many kinds of specifications.

Technical Parameter

Model	DZB-250D(E)30-150 PCS/Min.	DZB-400D(E)
Packing capacity	30-150 pcs/min.	30-150 pcs/min.
Bag size (mm)	L(60-190)×W(30-110) ×H(5-40)mm	L(60-190) ×W(30-180) ×H(5-60)
Max. width of film	250mm	400mm
Power supply	AC220V 50Hz, 2.4KW	AC220V 50Hz, 2.65KW
Weight	700kg	800kg
Overall dimension (LxWxH)	3350x1800x650 (mm)	3500x1800x800 (mm)