



HY-YS100 Fully Automatic Vertical Bag Packaging Machine



Applicable to the automatic packaging of liquid paste products in the cosmetics industry, such as: a black wash + double oxygen milk, shampoo + conditioner, shampoo + shower gel, etc.; divided into left and right compartments and front and back compartments, while measuring 2 Different materials.

Features:

1. Film on backside of machine and the molding is more stable;
2. Full pneumatic control including metering and bag making, simple operation, less wear parts in the later period, reducing parts replacement;
3. Material: The cabinet is made of SUS304 stainless steel, and the material contact part is made of SUS316L stainless steel, which is in line with GMP production.
4. The heat-generating parts and moving parts are hidden in the protective cover, which is safe and reliable.
5. The equipment is equipped with casters for easy handling and movement.

Mechanical characteristics and product characteristics:

1. It is specially designed for chemical products with high pH and alkali. The barrel is made of SUS316L stainless steel, and the PH value is up to 10 degrees. It is made of plastic barrel (bottled Yibao);
2. Two diaphragm pumps are used for automatic feeding, and the material is automatically fed, the material is completely stopped, the contact between the material and the air is reduced, and the manual feeding time is saved;
3. The packaging film of a black-washed product is quite special, and a high-strength and alkali-resistant material is required, and the intermediate film can satisfy the two-side heat sealing;

4. Single package and even package are required, cut by pneumatic cutting knife; single package is cut by rotary knife;
5. The heat-generating parts and moving parts are hidden in the protective cover, which is safe and reliable.

Technical Parameters

Model	HY-YS100/YS200/YS300
Filling range	(15+15) ml
Sachet size	W : 90mm,L:120mm
Max. film width	280mm/320mm/720mm
Sachet type	Four sides seal with double compartments
Filling method	Piston pump
Capacity	20-35ppm
Power Voltage and consumption	220V50-60HZ/1.5KW
Air pressure and consumption	0.3m ³ /min 0.6-0.8Mpa
Dimension(L*W*H)	1165*1319*1680mm
Weight	350KG