

High Speed of Automatic L-Side Sealing & Shrink Packaging Machine – CE-50H/SPR + CE-50



This model is the first fully automatic sealing and cutting shrink packaging machine with leading industry technology innovation. It can automatically complete the steps of feeding, filming, sealing and cutting, and shrinking. It has a high degree of automation and high work efficiency. It is truly dust-proof and moisture-proof, anti-tamper.

This full-servo close-joint sealing and shrinking machine is widely used in mass production packaging lines, including printing, color boxes, greeting cards, photo albums, photo frames, medicine, electronics, daily chemicals, cosmetics, auto parts, hardware, food and other industries.

Characteristics:

Sealing and cutting knife holder

- Cutter double column vertical movement, servo drive system makes sealing more stable

Self-adjusting height

- The opinion is that the height is set, and the packaging height can be adjusted arbitrarily with the applicable range to reduce the sealing knife store but achieve faster sealing and cutting efficiency

Photoelectric

- Using vertical + horizontal detection system, it can be more convenient to switch between different products

Wide range of applications

- The length is not universal and the speed is fast, especially suitable for large and small products

High automation program

– The machine head is driven by a servo + planetary gear box, and the heat shrinking machine adopts dual frequency conversion speed control.

The machine head has a thick conveying and tight connection function.

It automatically completes the steps of feeding, bagging and filming, sealing and cutting and heat shrinking. The automatic program control is high and the operation is simple. Convenient with safety protection and alarm functions.

Technical Parameter:

Model	CE-50H/SPR	CE-5030/LW
Name	L-Type Sealer	Shrink Tunnel
Brand	FULLWELL	FULLWELL
Voltage	220V, 50/60Hz	380v 50/60Hz
Power	3kw	16kw
Packing dimension	(L+H) ≤500mm (W+H) ≤400mm	(L)1200×(W)450×(H)250mm
Sealing size	L550 x W450mm	(L)1500×(W)500×(H)300mm
Packing speed	20~35 packs/min	20~60 packs/min
Air pressure	6-8kg/cm ³	6-8kg/cm ³
Max current	10A	32A
Weight	800kg	650kg
Overall dimension (L x W x H)	2050 x 1580 x 1740mm	2000 x 1100 x 1250mm