

DCFD-300 Tipping-bucket Type Automatic Back-Sealing Packing



This machine is applied to pack slice or bar type materials, such as preserved fruit, nut, and dried seafood etc.

Features

- Bag-making, measuring, filling, sealing, cutting, date inking, easy-off gap forming and Counting are all finished automatically, high effective and sanitary.
- Either under set length control or photoelectric color tracing, bag length is set and cut In one step. Time and film saving.
- The temperature is under independent PID control, more suitable for different packing Materials, the tolerance is $\pm 1\%$.
- Equip easy tear-off gap device, so there is an easy tear-off gap on each finished product.
- The driving system is simple and reliable, and maintenance is easy.
- Main parts are made of stainless steel, meet the GMP standard.
- Automatic self support lubricating system, the machine can continuous more than 24 Hours.
- Applicable material should be composite film like: PET/PE, Paper/PE, PET/AL (PET-AL), PE, OPP/PE etc.

Technical Parameters

Model	DCFD-300
Sealing type	back-sealing
Method of measurement	Manual work
Packing speed	40 - 60 bag/min
Bag size	W/10-140 mm, L/30-190 mm
Power	1.6 KW
Power supply	AC,220V/50HZ 1 phase or customization
Net weight	360 kg
Overall size	2500x730x1780 mm