

SHH-GZ Series Glass Bottle IV Infusion Filling Machine



The glass infusion bottle enters the filling part in the way of fixed distance and bottle separation after passing the bottle feeding track and twisting into the bottle. The filling is measured by the principle of time and constant current. The filling amount is set and adjusted by the touch screen, and the measurement is stable and accurate.

Performance characteristics:

- A. Filling station adopts the principle of constant pressure time measurement, filling response time precise fine-tuning (can be controlled in 0.01s), the load can be easily set and adjusted through the touch screen, the on-off valve adopts German pneumatic valve. Accurate filling measurement, the equipment can achieve no bottle no filling, filling pipeline can achieve in-place cleaning/in-place disinfection (CIP/SIP);
- B. The liquid level in the filling and storage barrel is automatically controlled, which can realize the automatic filling of the filling barrel;
- C. During the filling process, the mechanical parts have no compulsory friction, no particle pollution, and meet the requirements of GMP;
- D. Simple and convenient replacement specifications.

Technical Parameters:

Model	SHH-GZ16	SHH-GZ24
Application specification	50ml、100ml、250ml、500ml	
Production capacity	120 bottles/min	200 bottles/min
Filling head	16	24
Metering error	500ml $\leq\pm 1.0\%$; 250ml $\leq\pm 1.5\%$; 100ml $\leq\pm 2.0\%$; 50ml $\leq\pm 2\%$;	
Electric capacity (KW)	4.0KW	
Compressed air consumption (L/min)	1500 L/min	3000L/h
Overall size L*W*H (mm)	1290x1540x2300	1580x1870x2300

Model	SHH-GZ36	SHH-GZ48
Application specification	50ml、100ml、250ml、500ml	
Production capacity	300 bottles/min	420 bottles/min
Filling head	36	48
Metering error	500ml $\leq\pm 1.0\%$; 250ml $\leq\pm 1.5\%$; 100ml $\leq\pm 2.0\%$; 50ml $\leq\pm 2\%$;	
Electric capacity (KW)	4.0KW	
Compressed air consumption (L/min)	4000L/h	4500L/h
Overall size L*W*H (mm)	1900x2200x2300	2130x2600x2300