

ROY-10B PE Film Shrink Wrapping Machine



Shrink Wrapping Machine can apply to the full automatic packaging production line of beer, beverage, pure water, fruit juice, dairy products, etc.

Characteristics:

1. It is equipped with full automatic functions of bottle transferring and arrange, membrane packing, sealing and cutting, shrinking, cooling and shaping, etc.
2. The quick seal cooling structure guarantees that the seal has a higher strength even if under high speed production condition.
3. The inductive switch controls the membrane transfer system to reliably adjust and control membrane transferring length with less loss.
4. All the transfer system is controlled by frequency changing devices with stable and smooth transfer speed.
5. Unique thermal passage with centrifugal thermal air circulation system that has an equal heat distribution with beautiful and secure shrinkage effect.
6. 3 layers of heat insulation treatment with good insulating system that has an equal heat distribution with beautiful and secure shrinkage effect.
7. The enhanced cooling shaping passage can quickly turn the packaging membrane into high strength status that is conveniently stored and transported.

Technical Parameters

Dimension of the Whole Unit	L6500mm×W3200mm×W2100mm
Thermal Shrinkage Passage Dimension	L1800mm×W650mm×W450mm
Max. Package Dimension	L600mm×W400mm×W350mm
Packaging Speed	10-12 Pcs/min
Transfer Belt Dimension	530mm
Sealing and Cut Time /Temperature	0.5-1.5s 140°C-160°C
Operating Power Supply /Power	TN-S 380V 24KW
Operating Air Pressure	0.6-0.8 Mpa
Air Consumption	0.5 m³/min