



DXDF-150II Automatic Powder Filling Packing Machine



The machine is designed and manufactured specially for powdery and super fine powdery products. Driven by servomotor, the auger is rotating to fill products; furthermore, the filling range can be adjusted automatically through computer. The processes of bag making, measuring, filling, sealing, cutting, counting and hot pressing codes can be done automatically. Packing material include several kinds of heat-seal lamination, such as PET/plated AL/PE, PET/PE, NYLON etc.

Features:

1. All stainless steel cover meets to GMP standard.
2. Equipped with antipollution and dustproof device.
3. Automatic adjustment of pouch size and filling range.
4. Photocell controller is easy to manipulate.
5. The horizontal sealing uses high temperature resistant bearing which will ensure the continuous operation of the machine without filling the oil regularly.
6. The operation facility is controlled by American intel computer, all function is displayed with digital screen.
7. Minimum sealing temperature variation employs PID temperature, the tolerance is controlled by $\pm 2\%$.
8. Sealing part: roller spend process is special designed and the effect of sealing is very well.
9. Equipped with easy open system.
10. Equipped long filling screw make the sealing area clean and strong and compact shut-off door is used to prevent from product clamping at sealing jaw.

Specifications:

TYPE	DXDF-150II
Bag size	L70-150 /W70-115mm
Capacity	28-60 bags/min
Filling range	30-150 ml
Power	220V,50HZ,1.9KW
Weight	450 KGS
Dimension(L*W*H)	700x 800x1900 mm3(L*W*H)