

## ***BS-A450 Thermal Shrink Packaging Machine***



- BS-A450 thermal shrink packaging machine is suitable to shrink thin shrink films such as POF, PVC, PP, POP, etc with far-infrared radiation.
- The thickness of shrink film should be in the range of 0.01-0.04 mm.
- Quartz heating pipes are located on the top, bottom and sides of the shrinking tunnel.
- The temperature of the shrink room and the speed of the conveyer are adjustable.
- And the size of shrink tunnel can be customized.
- Conveyor has option of chain roller and iron net conveyor for choice.

### **Features:**

1. The lid can be open and bottom tray can be pulled out for the convenience of replacing heating pipes Compact construction, high efficiency;
2. Voltage of down heating pipes is adjustable through solid-booster, in order to control down temperature. The temperature of whole shrink tunnel is controlled through AC contactor.
3. Strong air-flow ensures excellent heat distribution for an even shrinking;
4. Intelligent temperature controlling system makes the operation easily;
5. The speed of the conveyer is adjustable.

### **Specification:**

Model	BS-A450
Power source	220V 50-60Hz
Power	9KW
Conveyor speed	0 -10m /min
Tunnel size(LxWxH)	830x450x 250mm
Conveyor loading	8kg
Machine size (LxWxH)	1350x780x 1380mm