

J500 Auto Stand-Up Round Bottle Labeling Machine



Description:

It adopts stand-up labeling method, and separates the bottles with separating wheel. When one bottle gets to the place of labeling and is detected by the transducer, the rubber pressing bottle device which is started by cylinder is pushed out, and make the bottle rotated at the labeling place. After that, the transducer of placing will detect one part which needs to label the sticker on the bottle. According to the labeling requests, it needs to fix some one time, and after getting to this time, the step-motor in the labeling head will send one sticker and label it on the fixed place by pressing.

Function:

It adopted the incorporate elements of ray, machine, electric and gas, it uses the most advanced touching display operation and can save many sets of information. You needn't to debug the machine and move the magic eye when you change the objects .It can label front and back stickers on the column form containers at the same time, and the label distance can be adjusted optionally; If it is circuit label, it will be handsome and paperbound, also with the high precision of superposition; It also can add the tape printer and finish the label printer at the same time . It is special suitable for the column form containers of wine, food, cosmetic and medicaments.

Technical Parameter:

- 1) Object to Apply: column form containers with one sticker or two stickers
- 2) Container Range (mm): Ø25—Ø120 Height: 50-300
- 3) Label Range (mm): Length 15-380 Height: 15-130
- 4) Label Speed (It bears on the size of the container and label) (pc / min): 0-50
- 5) Label Precision (mm): left to right: ± 1 Top to down (mm) : ± 0.5
- 6) Power: 220V 50/60HZ 0.25KW
- 7) Air Power: 5 kg/cm²
- 8) Weight (kg): 110
- 9) Measurement (mm) (Length*Width*Height): 1600*1100*1300

We can customize your order if you have special demands.

Main Character:

- It can use the label which is made by Chinese material, it reduces many label cost.
- It won't be affected by the objects' precision;
- It can save 8 kinds of labeling information; it doesn't need to debug and more the magic eye again when you change the labeling containers;
- The touching display, stimulant capacity adjustment and it has easy mechanical adjustment , need not the professional technical worker to operate ;
- It has the show of the day and total quantity;
- It can use stand-alone or join the production line;
- Adopt import electric components;
- Adopt 304 stainless steel and alloy which is dialed with anodic oxidation except the shelf.