

YS-SS-2520-IP-3S(4S)-ZIP Vertical Packaging Machine



- This series machine is very popular, it can be integrated with various filling systems, suitable for many kinds of products.
- Continuous pull film movement, Simple structure, Economical and practical
- Continuous motion leads to high productivity
- Lean machine concept enables cost-effective production
- Maintenance-free servo-technology ensures reliable production
- PLC controls enable precise machine movements for smooth production and good bag quality
- Intuitive HMI allows easy operation and short training time
- Open machine concept for easy access and maintenance
- Compact machine design for good ergonomics, product-conserving filling and saving space

Technical Parameters

Model	YS-2520-IP-3S-ZIP	YS-SS-2520-IP-4S-ZIP
Bag type	3-side sealed bag	4-side sealed bag
Standard capacity	10-45 bags/min	10-45 bags/min
Bag size	Width : 60-400mm	Width : 60-400mm
	Length: 60-260mm	Length:60-260mm
Film parameter	packaging material:OPP/AL/PE, PET/VMPET etc.	
	Film diameter: ≤600mm	
	Core diameter:76mm	
Total power	5 KW	
Air pressure	≥0.5MPa	
Air consumption	HS closure, 0.32NL/cycle	
Outer dimensions (appr.)	1800*1270*1615mm	
Weight (appr.)	680kg	
Power supply (optional)	3N-PN-50Hz 380V/220V (3P 5 wires)	