

BTB-200S Three-dimensional Packaging Machine



Product description

1. The machine adopts multi station turntable alternative packaging mode, all wrapping and heat sealing actions are completed by cam drive, with the characteristics of fast speed and stable operation.
2. The frequency converter is used to adjust the packing speed, which can reach 30-60 packages / min according to the different packing items.
3. Changing the mold can pack different sizes of items. The patented structure of the design makes it easier and faster to replace the mold.
4. It is equipped with double side wrinkle skirt shaping and beauty device, which makes the film packaging more close to the body and more beautiful.
5. Using the new double rotary film cutter, the service life is increased by 5 times, and the film cutting is more accurate and smooth.
6. It has the function of anti-counterfeiting and unsealing line with laser anti-counterfeiting and anti-moisture function.
7. Equipped with static eliminator, it can effectively eliminate the static electricity adsorbed on the packaging film and make the film delivery more smooth.
8. By changing the feeding mode, it can be connected with the automatic unmanned production line.

Technical Parameters

Packaging	BOPP smoke film and gold wire
Packing speed	30-80 bag/min
Maximum package size	(L)300×(W)120×(H)60mm
Power supply and total power	220V 50Hz 5kw
Weight	600Kg
Dimensions	(L)2000×(W)800×(H)1400mm
Film width	≤200mm