

Automatic Banding Machine WK04-30ABE



Ideal for integration with systems such as an inline receding offset stacker, three knife trimmer, product feeders, lugged conveyors, or other such applications. The WK04-30ABE uses a mechanized pusher combined with bidirectional jogging and pneumatically powered clamp to ensure products are neatly stacked before they are automatically banded. Setup is easy using a 6.25" Schneider touch screens. The AHS-430 MAG easily rolls up to your system and with a few adjustments is ready to start saving you time and unwanted handling of loose product.

- Bands products with Paper Tape or Plastic Film
- Completely automated and highly efficient process
- Automatic bi-directional Jog function make sure your products stay neat
- Pneumatically operated clamp compresses products
- Adjustable Clamp Pressure
- Easily adjustable side guides
- 6.25" Schneider touch screen make job setup easy
- Four Casters on the WK04-30ABE increase its mobility
- Leveling feet allow you to match the machine's height to your application
- Grooved rollers ensure your product is fed correctly to the bander

Specifications:

pe Width	Available in 20 mm (.78") 30 mm (1.18") 40 mm (1.57") 50 mm (1.96")
Tape Thickness	Plastic: 50-80 μ Paper: 120 μ
Material	Kraft Paper Banding or Plastic Banding Film
Net Weight	661 lbs (300 kg)
Welding Method	Heat Sealing
Banding Tension	5-50 N
Speed	Up to 15 per min
Product Height	0.5 to 18 cm
Product Width	0.5 to 32 cm
Product Length	10 to 48 cm
Power	110 Volt, 1500 Watt, 13.6 Amps
Machine Size	54.5" long (138.5 cm) x 38" wide (96.5 cm) x 65" high (164.5 cm)