

GPC-60 Doypack Bag Packaging Machine



- Front reels loading
- Machine with reduced sizes and higher output
- Self-supported frame, clean and without holes
- Standard stainless execution
- Reel shafts expandable without toolings
- Parallel sealings
- Low inertia cams
- Low maintenance and high durability cutting device
- Net electrical configuration
- Remote tele assistance
- Simplex, duplex, triplex and quadruplex machine
- Continuous unwinding
- Formats memory programmed in recipes

Filling stations	3	3	2-3	2-3	2-3	2-3	2-3
Maximum volume (1)	2000cc	1500cc	750CC	500CC			
Outside reel diameter	800mm	800mm	800mm	800 mm	800mm	800mm	800mm
Core reel diameter	70-75 mm / 150-155 mm						
Maximum output	50 cycles/min.	100 cycles/min.	150 cycles/min.	200 cycles/min.			
Power consumption (1)	50 kw (aprox)						
Air consumption (1)	400 l./min. (aprox.)						

(1) Depending on product, film, formats and final machine configuration.

SACHET RANGE DIMENSIONS

Simplex		Duplex		Triplex		Quadruplex	
MAX.	MIN.	MAX.	MIN.	MAX.	MIN.	MAX.	MIN.
250	75	200	75	130	75	100	75
320	100	320	100	320	100	320	100
50 sachets/min. (3000 h)		100 sachets/min. (6000 h)		150 sachets/min. (9000 h)		400 sachets/min. (24000 h)	

