



TB-series Fully Automatic Shrink Film Label Machine



Equipment features:

1. The whole machine is made of stainless steel and high-quality aluminum alloy, with a reasonable, compact structure and easy adjustment;
2. No need for anchor bolts, it can be easily moved and flexibly matched with the production site;
3. Shrink film label holder, easy to adjust according to different label paper tubes ranging from 5" to 10";
4. No tools required, the transmission mechanism can be easily adjusted and suitable for different bottle types;
5. The labeling method is unique, using a compression labeling method that is both convenient and reasonable;
6. Label cutting detection system to ensure the lowest error;
7. The uniquely designed cutter head, within the specified range, can be replaced without changing the cutter holder, making tool changes fast and convenient;
8. The center column clamping system allows for quick replacement without the need for any tools;
9. The bottle dividing screw, positioning belt, and conveyor chain adopt synchronous adjustment method, making speed adjustment simple and fast;
10. Using Japanese servo motors and high-sensitivity optoelectronics, the cutting length is precise.

Technical Parameters

主要技术参数 Main Technical parameters				
机型	Model	TB-150/STB150	TB-250/STB250	TB-350/STB350
长X宽X高(mm)	Dimensions (LxWxH)	2400×1000×2200	2440×1000×2200	2440×1000×2200
重量	Weight	600kg	600kg	700kg
电源	Electric power	AC3-Phase 220V/380V	AC3-Phase 220V/380V	AC3-Phase 220V/380V
速度	Speed	UP to 200BPM	UP to 300BPM	UP to 400BPM
高度	Hight	MAX 320mm	MAX 320mm	MAX 320mm
直径	Diameter	Φ50-Φ110	Φ50-Φ110	Φ50-Φ110
材质	Materials	玻璃、金属、塑胶 GLASS, METAL PLASTIC		
形状	Shapes	圆、椭圆、方型、长方形 ROUND, OVAL, SQUARE, RECTANGLE		
材质	Materials	PVC, PET, OPS, OPP		
厚度	Thickness	0.035-0.10mm	0.035-0.10mm	0.035-0.10mm
标签长度	Length	MAX 150mm	MAX 150mm	MAX 200mm
标签折径	Flat width	MAX 175mm	MAX 175mm	MAX 175mm