

Combination Shrinking Machine/Shrink Tunnel FL5545T+SM4525

L bar sealer specification

Scope of Application:

- Suitable for electrical products, hardwires, software's, food, printing products, medications, floor boards, ceramics etc's packing.
- Suitable for PVC, POF, PP film's using.

Model	FL-5545T
Machine dimension L×W×H (mm)	1560×725×1040
Max packing size L×W×H (mm)	450×400×250
Max sealing size L×W×H (mm)	550×450
Packing speed (pcs/h)	800-1200
Net weight (kg)	125
Power (kw)	1.2
Power supply	1f110V/220V 50/60Hz

SM4525 Shrinking tunnel Technical instruction:

- All switches and units are original from famous manufactory, the performances are stable.
- Free to adjust the speed of conveyor belt by electronic speed controller.

- The surface of machine would not over heat because it is equipped with double insulated device.
- Import insulated curtain which be able to resist high temperature in order to reduce energy wasting.
- It adopts stainless steel heater to heat up quickly, and equipped with large power blowing motor to keep big flowing but evenly. Conveying speed or tunnel's temperature can be freely adjustable according to the size of products and output.
- Convey chain is made of solid poles covered by silica gel tube, to bear such objects in heavy and would not be distorted.
- Such various shrink film as PVC/PP/POF are applicable.

Model	SM-4525
Machine's dimension L×W×H(mm)	1300×715×1455
Max packaging size L×W×H(mm)	700×400×200
Size of tunnel L×W×H(mm)	1000×450×250
Packing speed (pcs/h)	2000-3000
Net Weight (kg)	185
Power (kw)	8
Power supply	3f220V/380V 50/60Hz