

Stirring Blender CW Series



Stirring Blender is designed based on double cone mixer and adds stirring unit, which can be used for material in pharmaceutical, foodstuff, chemical industry and feed stuff etc.

Features:

Stirring Blender can rapidly mix materials as easy clot and with certain water content, having high mixing speed and good mixing effect. The mixing uniformity rate can reach over 95%. Inner of this machine is of new type sealing structure. During mixing, it is free of pollution. CW Series Stirring Type Blender is of simple structure and convenient operation and maintenance.

Technical Parameters:

| Model | Barrel volume (L) | Max. loading volume (L) | Max. loading weigh (kg) | Mixing motor (KW) | Stirring motor (KW) | Mixing rotary speed (r/min) | Stirring rotary speed (r/min) |
|---------|-------------------------|----------------------------------|----------------------------------|-------------------------|---------------------------|--------------------------------------|--|
| CW-50 | 50 | 25 | 25 | 1.1 | 0.75 | 20 | 60 |
| CW-100 | 100 | 50 | 50 | 1.5 | 1.1 | 20 | 60 |
| CW-200 | 200 | 100 | 100 | 2.2 | 1.1 | 20 | 60 |
| CW-300 | 300 | 150 | 150 | 2.2 | 1.1 | 20 | 60 |
| CW-500 | 500 | 250 | 250 | 3 | 2.2 | 20 | 60 |
| CW-1000 | 1000 | 500 | 500 | 5.5 | 2.2 | 10 | 40 |
| CW-1500 | 1500 | 750 | 750 | 7.5 | 4 | 10 | 40 |
| CW-2000 | 2000 | 1000 | 1000 | 7.5 | 4 | 8 | 30 |
| CW-2500 | 2500 | 1250 | 1250 | 11 | 5.5 | 6 | 20 |
| CW-3000 | 3000 | 1500 | 1500 | 11 | 5.5 | 6 | 20 |
| CW-4000 | 4000 | 2000 | 2000 | 15 | 7.5 | 6 | 20 |
| CW-5000 | 5000 | 2500 | 2500 | 15 | 7.5 | 5 | 20 |
| CW-6000 | 6000 | 3000 | 3000 | 17.5 | 7.5 | 5 | 20 |