

High Speed Side Sealing Shrinking Machine FL-5545TBH+SM4525LH



Technical features

FL-5545TBH Hi-speed sealing machine can be combined with an automatic production line for shrink wrapping, adopts photo electricity for inducing the products, there are two feed-in modes, auto/man, use fold film on rolls, and the machine will seal other three sides automatically. According to different collocations for the machine and different products, the max packing speed is up to 45 pcs/min.

Constant temperature heat sealing and cutting system is suitable for PE. PVC. POF etc, industrial standard shrink films, the seal is firm and nice, especially applicable for POF film, adjust the conveyor with the head wheel for packing products of different size. The reliability is higher and easier to operate it.

The front feed in systems speed is adjustable, combines a worktable at the end of the tunnel, makes whole machine highly automatic, it runs automatically without an operator comes true. SM-4525LH Hi-speed hot air circulating shrink tunnel adopts roller type conveyor, the rollers are covered by silicone gel pipe, they roll automatically, also the conveyor can use Teflon mesh belt or S.S. mesh belt instead of rollers. When shrink PE film, need not the rollers roll, easy to convert it by the handle at the end of the tunnel.

The temperature inside the tunnel is even, suitable for shrink PE.PVC.POF films. The inner container forms hot air circulation inside tunnel, the volume of hot air can be controlled by the air doors according to the packing requirements for different products.

Model	FL-5545TBH
Machine dimension L×W×H (mm)	2050×1580×1740
Max packing size L×W×H (mm)	Unlimited×300×150
Product W+H	450
/tunnel size (mm)	
Packing speed (pcs/min)	20~60
Net weight (kg)	800
Power (kw)	3
Power supply	3f220V/380V 50/60Hz
Air pressure (kg/cm3)	5.5
Max current	10:00 AM