



Automatic Shrink Packing Machine QSJ-5040A



The QSJ-5040A Automatic Sleeve Wrapper bottle packing machine+BSE-5040A Heat Shrink Tunnel adopts the advanced touch screen which makes operation easier, 'Omron' programmable logic controller (PLC) and AC contactor, 'AirTAC' cylinder, and all the rest parts adopt international famous brand.

Upper and down electromagnetic switch prevents sealing mistakes, and protect operator. Automatic alarm security system protects machine and operator.

Large power conveyer motor, with stepless speed regulating, ensures smooth feeding.

Two large power fans make the temperature of shrink tunnel every even and stable, this ensures the excellent effect of shrinking in one time.

Super cooling system cools the packing and makes the figuration perfectly.

Main Technical Data:

Model	QSJ-5040A
Power source	3phase 380V 50HZ
Power	3KW
Capacity	0-8 packs/min
Working air pressure	0.4 -0. 6 MPa
Width/thickness of the film	Max. 590mm/0.03 - 0.25mm
Max. packing dimension(L*W*H)	420*300*350mm
Min. packing dimension(L*W*H)	250*50*100mm
Conveyor driver size (L*W*H)	900*306*800mm
	1700*306*800mm
Machine size(L*W*H)	1060*1600*1930mm
Machine weight	370KGS

Model	BSE-5040A	BSE-6040A
Power source	220V/380V-460V	220V/380V-460V
	50-60HZ 3phase	50-60HZ 3phase
Heater power	20KW	20KW
Conveyer speed	0-10m/minute	0-10m/minute
Tunnel size(L*W*H)	1500*500*460mm	1500*600*460mm
Conveyer loading	30KGS Max.	30KGS Max.
Machine size(L*W*H)	2500*820*1680mm	2500*920*1680mm
Machine weight	470KGS	500KGS
Shrink film	PE,POF,PVC,PP	PE,POF,PVC,PP