

Inline Trunnion Series Labeling System



The NEW Label-Aire® Trunnion Series labeling system accurately wrap applies labels at high speeds to small diameter products at an affordable price. Trunnion labeling has never been easier!

Based on the industry-proven stainless steel cabinet based Inline Series 5100 labeling system, the Trunnion Series continues Label-Aire's longstanding tradition of advanced features, toughness, speed, and accuracy spelling lower operating costs and increased productivity for your operation. The Trunnion Series is specifically designed to handle non-stable cylindrical containers or products (i.e., top heavy or rounded bottom) including vials, ampoules, lip balm/lipstick containers, small batteries, crayons, pens, etc.

The NEW advanced yet rugged Trunnion Series labeling system is a stainless steel cabinet based PLC-controlled labeling system designed for heavy duty wrap labeling applications. The Trunnion Series can be specifically built for horizontal-, vertical-, or angled trunnion labeling. Among its standard features are a rotating control panel and a 6 foot (1,828.8 mm) trunnion roller conveyor with stainless steel side plates. An 8 foot (2,438.4 mm) trunnion roller conveyor is optional. Other standard features include Automatic Speed Following (ASF) for product surface profiling, Variable Frequency Drive (VFD), and tilt adjustments for maximum versatility. The Trunnion Series' long list of options include a choice of Label-Aire New Generation 3100/3000 Series applicators, wrap belt, stainless steel side plates, stainless steel frame, and stainless steel cabinet.

Put this proven trunnion labeling technology to work for you all day, every day. The Trunnion Series is built to meticulous quality standards and designed to work in the most hostile environments.

Main Drive:	Variable Frequency Drive (VFD)
Line Speed	up to 1,200" (30.48 m) per minute
Construction:	
Frame	Stainless Steel
Cabinet	Stainless Steel
Conveyor:	Stainless Steel Side Plates
Width	Consult Factory
LengthHeight	6' (1,828.8 mm center line-to-center line),
	8' (2,438.2 mm) length optional
	36" (914.4 mm) ±2" (50.8 mm)
Applicator:	Label-Aire 3100/3000 Series Primary Applicators
Operator Interface:	VFD Speed Control
Control	Push Button Start/Stop
Wrap Belt:	Consult Factory
Drive	VFD