

Automatic Sleeve Shrink Wrapping Machine YC-6030AH / 6040E



Automatic sleeve sealing and shrinking machine is an efficient sleeve sealer packaging machine, easy to control. Based on different requirements to choose to push the product automatically, sleeve sealer is fit for packaging single product or groups of products, such as, cartons, beverage, cosmetics and electronic products.

Features:

- This automatic sleeve shrink wrapping machine is designed for single objects or products without support. After the machine is docked with the production line, it automatically feeds, wraps, seals and cuts, shrinks, and cools and sets. It is a set of automatic packaging equipment without manual operation. Can make 6 bottles (2*3), 8 bottles (2*4), 9 bottles (3*3), 12 bottles (3*4), 15 bottles (3*6), 18 bottles (3*6) , 20 bottles (4*5), 24 bottles (4*6) and other packaging forms;
- JM-6030AH introduces international advanced technology and craftsmanship, with stable and reliable equipment performance, automatic counting of daily output and other functions;
- Use PLC programmable program controller and intelligent touch screen to realize the integration of machine, electricity and gas;
- This machine can carry out two-row, three-row, four-row heat shrink packaging without bottom support according to the production requirements. When the packaging form is changed, only the switch on the panel needs to be changed;
- The geared motor is used to ensure smooth and no jitter during feeding and film feeding. When packaging color films, a color code positioning system needs to be added for accurate positioning;
- Specially designed sealing knife is adopted, the sealing line is firm, does not crack, and is not easy to stick to the knife;

- The feeding conveyor belt can be designed to feed on the left or the right according to the needs of the site;
- JM-6040E adopts imported dual-air blower motor to make the hot air spread evenly in the furnace cavity, and the effect after shrinking is more beautiful;
- Adopting solid steel rod outsourcing imported silicone tube, chain rod conveying is durable. Conveyor chains of different materials can also be used according to different products;
- Adopt French Schneider inverter to control the transmission speed, stepless speed regulation;
- Ultra-large air volume cooling system, the product is quickly cooled and shaped after shrinking, and the rear end can be equipped with an aluminum workbench, so that the product will not fall to the ground after packaging;
- It is suitable for sealing and cutting shrink packaging of round products such as beer, mineral water, cans, glass bottles and plastic bottles without pallet.

Technical Parameters:

Model	YC-6030AH	YC-6040E
Maximum packaging size	L300mm*W500mm*H300mm	L1500mm*W500mm*H300mm
Sealing knife length Oven cavity size	670mm	1800mm*500mm*300MM
Packing speed	12M/min	0-15M/min
Applicable shrink film	PE	PE
External air source	6-8KG/Cm ²	6-8KG/Cm ²
Power	18KW	18KW
Power supply	220V 1/3PH 50/60HZ 1.8KW	380/220V 3PH 50/60HZ
Mechanical Dimensions	L2875mm*W1378mm*H1813mm	L2800mm*W950*H1750mm
Weight	620KG	625KG