



HY-118 Liquid Filling Machine



Features

1. This machine works steadily and continuously, and is suitable for various oral liquids, essential oils and liquid products
2. Full automatic filling, photoelectric correction, no burr, integrated molding.
3. The equipment can be customized as required.
4. Adopting Panasonic PLC imported from Japan, the accuracy is improved and the stability of the equipment is high.
5. Intermittent sealing is better to ensure the beauty of sealing and avoid leakage.
6. This machine is easy to operate. PLC touch screen can adjust the packaging temperature and speed according to the packaging material, product thickness and length. Servo motor. Through the control of light, electricity and gas, the fault can be self diagnosed and displayed clearly. The operating system language can be Spanish, French, Korean, Russian, Japanese, Arabic and other local languages.
7. The whole machine is covered with stainless steel, with good appearance, easy to clean and durable. Low operation and maintenance cost.
8. Intelligent PLC temperature control.
9. The required number of automatic alarm reminders, the required number of automatic batching and stacking.
10. Free switching of product specifications

Technical Parameters

Model	HY118
Production speed	100-150 packs / min
Bag packaging type	Four side seal
Product size	Depending on the mold
Film width calculation formula	Depending on the mold
Bag length calculation formula	Depending on the mold
Packaging film width	≤118mm
Outer diameter of packaging film	≤400mm
Packaging film material	PVC PET
Air pressure	6Mpa
Total power	5KW
Power type	380kW, 50 / 60Hz, three-phase
Machine weight	880kg
Machine size	2300x850x1500mm (length x width x height)